

Cybersecure UxS Controller

IronClad is a low SWaP-C, cybersecure, platform-agnostic, UxS controller that can be easily upgraded or modified to support a variety of missions. Developed in collaboration with the Department of Defense and the Department of Homeland Security, the IronClad controller is American-Made, making it an ideal solution for OEMs searching for a vetted capability applicable to multi-rotor, fixed-wing and hybrid UAS, as well as ground and maritime robots.

American-Designed, -Made, & -Vetted

IronClad was developed in collaboration with the US Department of Defense and the US Department of Homeland Security – making it a highly-vetted capability. The IronClad UxS controller is designed and made by American engineers at CTI's facility in Dublin, Ohio.

Platform Agnostic & Modular

IronClad UxS controllers are suitable for Multi-Rotor UAS, Fixed-Wing UAS, Hybrid UAS, Ground Robots, and Maritime Robots. Its modular design allows for simple base configuration or platformspecific expansion boards.

Robust Embedded Hardware

IronClad includes robust CPUs/GPUs allowing for advanced autonomy features, video processing/conversion, and a variety of other applications requiring onboard computing modules.



6161 Riverside Drive Dublin, OH 43017 USA

SPECIFICATIONS

Origin

United States of America NDAA 2020 Section 848 Compliant

Platforms

Multi-Rotor UAS Fixed-Wing UAS Hybrid UAS Ground Robots Maritime Robots

Software

Advanced, Open-Source + Security Enhancements

Security

High Assurance Boot Encrypted File System ➤ Data at Rest Onboard AES-256 Encryption ➤ C2/Telemetry Data

- Auto-Wipe Encryption Keys
 - Tamper Events
 - Lost Vehicle
 - Crashed Vehicle

Embedded Hardware Robust CPUs/GPUs

Integrations Android Tactial Assault Kit (ATAK)



614.571.4102 ironclad@ctic.us www.ctic.us





IRONCLAD BENEFITS

Security: Embedded hardware and firmware security. "Security Umbrella" for payloads and applications. Vetted by DoD and DHS. Passed multiple DoD and 3rd-Party security assessments.

Extra Computing directly on the Board: Edge-computer capability for combined flight control, video processing, and AI/ML applications.

Service Life Extension: Extend the service life and upgrade the capabilities of older UAS through retrofitting.

Common Interface for Mixed UAS Fleets: Reduces training time and reduces the quantity and variety of ground control equipment necessary on-site.

Reduce Number of Operators Required: For complex tracking and targeting tasks.

Open-Source Autopilot Software:

Autopilot software is vetted and allows for tailored packages. Software is informed by academic and industry research. Can be considered Government-Off-The-Shelf (GOTS) system.

Modular Design: Additional processor types and digital I/Os can easily be added to IronClad via expansion ports.

Integrated HWIL Simulation Capability: Hardware-In-The-Loop Simulation capability allows for risk-reduced flight control refinement and payload development testing.



WHERE CAN IRONCLAD BE USED?

Service Life Extension: Retrofit kits are available for fielded DoD sUAS.

Program of Record: Common ground control station interfaces, flight controls, mission planning, cybersecurity Authority to Operate (ATO), training, and logistics.

R&D Contracts: Fault- and Damagetolerant flight controls, onboard collision avoidance autonomy packages, and capabilities to enable autonomous flights in urban and other severe geographic environments.

OEM Integration: Upgrade from Pixhawk hardware while using the same codebase.



Size: Dimensions – 4.4" x 2.2" x 1.0" Weight – 75g (Enclosed Ki<u>t – 150g)</u>

FMU Computer Specs:

Main Cores > 4 x Arm Cortex-A53 @ 1.6Chz > 1 x Arm Cortex-M7 @ 800 Mhz Neural Processing Unit > Up to 2.3 TOPS Graphics Processing Unit > 16GFLOPS (high precision) OpenCL[™] 1.2 FP, OpenVG[™] 1.1 Video Processing Unit > Hardware Video Encoding Crvptographic Acceleration & Assurance

True Random # Generator
Symmetric – AES-128/192/256
Asymmetric – RSA (up to 4096),

Elliptic Curve (up to 1023)

Onboard Sensors: 3 x IMUs, Temp-Controlled, 9DOF

2 x Barometer

Environmental: -40°C to 85°C

Electrical: Input Voltage - 4-40V DC

Expansion:

Gigabit Ethernet RGMII MIPI-CSI2 4-lane (x2) HDMI Output USB 2.0 & USB 3.0 PCI 2.0 1-Lane





Retrofit Kit for AE RQ-20 A/B



6161 Riverside Drive Dublin, OH 43017 USA 614.571.4102 ironclad@ctic.us www.ctic.us